

**AMENDMENTS TO THE CLAIMS**

Please **AMEND** claims 1-18, as shown below.

Please **ADD** claims 34-36, as shown below.

The following is a complete list of all claims in this application.

1. (Currently Amended) A liquid crystal display (LCD) module, comprising:  
a mold frame comprising a main panel, side walls surrounding the main panel and for sequentially receiving a back light assembly having a light source for providing light and a display unit for displaying images using the light from the back light assembly, said mold frame having a first engaging hole formed through the main panel on a bottom surface thereof; and  
a backlight assembly disposed on an upper surface of the main panel and comprising a light source;  
a display unit disposed on the backlight assembly; and  
a top chassis engaged with ~~said~~ the mold frame ~~such that said the top chassis is opposite to the mold frame, for guiding the position of~~ to fix the backlight assembly and the display unit therebetween, the top chassis having a second engaging hole formed ~~at a position~~ corresponding to the first engaging hole.
2. (Currently Amended) The LCD ~~A liquid crystal display module according to of~~ claim 1, wherein the light source comprises:  
a lamp ~~for generating the light;~~

a lamp holder engaged with both ends of the lamp ~~for fixing to fix~~ the position of the lamp; and

a lamp cover ~~for covering and protecting~~ the lamp.

3. (Currently Amended) ~~The LCD A liquid crystal display module according to of~~ claim 2, wherein the first engaging hole is ~~at least~~ overlapped with the lamp cover when viewed from ~~the a side of the mold frame where on which~~ the lamp is positioned ~~in the mold frame~~.

4. (Currently Amended) ~~The LCD A liquid crystal display module according to of~~ claim 1, further comprising a back cover ~~engaged with~~ disposed on a the rear surface of the main panel mold frame, and

wherein a third engaging hole is formed at a position on the back cover corresponding to the first engaging hole of the mold frame.

5. (Currently Amended) ~~The LCD A liquid crystal display module according to of~~ claim 1, wherein a plurality of the first and second engaging holes are formed in ~~an end portion~~ of the mold frame and ~~the bottom surface of the top chassis, respectively~~.

6. (Currently Amended) A liquid crystal display device, comprising:  
a liquid crystal display module mold frame comprising a main panel, sidewalls surrounding the main panel and ~~for sequentially receiving a back light assembly having a light source for providing light and a display unit for receiving the light from the back light assembly~~

~~and displaying an image, said liquid crystal display module with a receiving receptacle having a first engaging hole~~ formed through the main panel on a bottom surface thereof and;

a backlight assembly disposed on an upper surface of the main panel and comprising a light source;

a display panel disposed on the backlight assembly;

~~a top chassis, in which a second engaging hole is formed at a position corresponding to the first engaging hole, being engaged with the receiving receptacle~~ mold frame such that it is opposite to the receiving receptacle to fix guide the position of the display unit and the backlight assembly therebetween, the top chassis having a second engaging hole formed corresponding to the first engaging hole;

~~a case for receiving the top chassis, said case having a catching member; and~~

~~an engaging device having an one end engaged with the catching member, the engaging device penetrating through the first and second engaging holes, for fixing to assemble the receiving receptacle~~ mold frame and the top chassis, one side of said engaging device being engaged with the catching member.

7. (Currently Amended) The A-liquid crystal display device according to of claim 6, wherein the light source comprises;

a lamp for generating light;

a lamp holder engaged with both ends of the lamp for fixing to fix the position of the lamp; and

a lamp cover for covering and protecting the lamp.

8. (Currently Amended) ~~The A-liquid-crystal~~ display device ~~according to~~ of claim 7, wherein the first engaging hole is overlapped ~~at least~~ with the lamp cover when viewed from ~~the~~ a side where the lamp is positioned ~~in the mold frame~~.

9. (Currently Amended) ~~The A-liquid-crystal~~ display device ~~according to~~ of claim 6, further comprising wherein the bottom surface of the receiving receptacle is one of the mold frame and a back cover formed on a bottom surface of the mold frame.

10. (Currently Amended) ~~The A-liquid-crystal~~ display device ~~according to~~ of claim 6, wherein a plurality of the catching member ~~is~~ members are formed ~~at both end portions of the inner side~~ on an bottom surface of the case.

11. (Currently Amended) ~~The A-liquid-crystal~~ display device ~~according to~~ of claim 6, wherein the catching member is integrally formed with the case and ~~is~~ comprises a support surface extending from ~~the side wall of the case~~ and in parallel to ~~the~~ a bottom surface of the case.

12. (Currently Amended) ~~The A-liquid-crystal~~ display device ~~according to~~ of claim 11, wherein the catching member further comprises a through-hole formed at a center portion of the support surface and receiving an end ~~for receiving one side of the engaging device is formed at a central portion of the support surface.~~

13. (Currently Amended) ~~The A-liquid-crystal display device according to~~ of claim 12, wherein the catching member further comprises a guide recess formed extending from the through hole to a side of the support surface for guiding the engaging device to the through-hole ~~is formed from the through hole of the support surface in a direction of an end portion of one side of the support surface.~~

14. (Currently Amended) ~~The A-liquid-crystal display device according to~~ of claim 13, wherein the engaging ~~means~~ device comprises:

a first engaging member ~~having~~ comprising:

a head portion wider than the through-hole and engaged with the catching member ~~to prevent the deviation from the through hole of the support surface and;~~

a body portion penetrating through the first and second engaging holes and protruding ~~to the rear~~ from a bottom surface of the ~~receiving-receptacle~~ mold frame ~~and having; and~~

a an end portion having screw recess ~~at one end portion thereof;~~ and

a second engaging ~~device~~ member engaged with the screw recess of the first engaging member to fix the mold frame ~~receiving-receptacle~~ and the top chassis to the case.

15. (Currently Amended) ~~The A-liquid-crystal display device according to~~ of claim 14, wherein ~~a first direction of a region adjacent to the head portion in~~ a portion of the body ~~portion of the first engaging member~~ adjacent to the head portion has a first thickness between a first side and a second side ~~is thinner~~ smaller than ~~the~~ a width of the guide recess ~~to slide the first~~

~~engaging member into the guide recess of the catching member and to insert the first engaging member into the through hole.~~

16. (Currently Amended) ~~The A-liquid crystal display device according to~~ of claim 15, wherein ~~a second direction parallel to the head portion of a region adjacent to the head portion in~~ the portion of the body portion adjacent to the head portion has a second thickness between a third side and a fourth side of the first engaging member and perpendicular to the first direction is wider greater ~~than the width of the guide recess to prevent the deviation of the engaging member from the through hole.~~

17. (Currently Amended) ~~The A-liquid crystal display device according to~~ of claim 6, wherein comprising a plurality of the first engaging hole holes and a plurality of the second engaging hole holes ~~are formed.~~

18. (Currently Amended) ~~The A-liquid crystal display device according to~~ of claim 6, wherein the case is ~~one of a front case and a rear case.~~

19-33. (Withdrawn)

34. (New) The display device of claim 9, wherein the back cover has a third engaging hole positioned corresponding to the first engaging hole.

35. (New) The display device of claim 34, wherein the engaging device penetrates through the first engaging hole, the second engaging hole and the third engaging hole.

36. (New) A display module, comprising:  
a mold frame comprising a main panel, side walls surrounding the main panel and a first hole formed through the main panel;  
a backlight assembly disposed on the mold frame;  
a display panel disposed on the backlight assembly;  
a top chassis disposed on the display panel and having a second hole formed corresponding to the first hole; and  
an engaging device penetrating through the first hole and the second hole to fix the backlight assembly and the display panel between the mold frame and the top chassis.